## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1-33. (Cancelled)

34. (Currently amended) A radio access network having a first communication protocol, said radio access network defining first cells at least some of which neighbor foreign cells employing a foreign communication protocol different from said first communication protocol, said foreign communication protocol associated with a foreign communication system, the radio access network comprising:

a radio access network node structure for communicating with a multi-mode mobile radio in said first cells;

a data mechanism for exchanging handover information through said network node structure with said multi-mode radio as said multi-mode radio is to be handed-over to at least one of said foreign cells, said data mechanism comprising a container structure comprising content expressed in the foreign communications protocol so that the node structure can serve as a conduit for the container and need not understand the content of the container structure; and A radio access network as in claim 27,

wherein the container structure comprises a dedicated data mapped structure generic to said radio access network and said foreign communication system such that said generic data mapped structure transports both handover data content unique to said first communication protocol and handover data content unique to said foreign communication protocol.

35. (Currently amended) A mobile radio network is in claim [[27]] <u>34</u>, wherein the radio access network node fills the container structure to include broadcast system information.

EUS/GJ/P/10-7525

36. (Currently amended) A mobile radio network is in claim [[27]] 34, wherein the

multi-mode radio fills the container structure to include mobile radio capabilities

information.

37. (Currently amended) A mobile radio network is in claim [[27]] 34, wherein the

radio access network node fills the container structure to include neighboring cell

information.

38. (Currently amended) A mobile radio network is in claim [[27]] 34, wherein the

radio access network node fills the container structure to include neighboring cell

measurement instructions.

39. (Currently amended) A mobile radio network is in claim [[27]] 34, wherein the

radio access network node fills the container structure to include neighboring cell

measurement instructions.

40. (Currently amended) A mobile radio network is in claim [[27]] 34, wherein the

radio access network node fills the container structure to include handoff command

information.

41-47. (Cancelled)

48. (Currently amended) A mobile radio network, comprising:

a radio access network having an associated first communication protocol for

communicating to a multi-mode mobile radio in first cells serviced by said radio access

network according to said first communication protocol:

a second network having an associated foreign communication protocol for

communicating to the multi-mode mobile radio in at least foreign cells neighboring said

first cells and serviced by said second network according to said foreign communication

protocol, said radio network and said second network being in handoff communication

Page 3 of 13

Appl. No. 09/286,471

Amdt. Dated November 4, 2010 Reply to Office action of November 4, 2009

Attorney Docket No. P11300-US1

EUS/GJ/P/10-7525

with each other to handoff said mobile radio when said mobile radio commutes from one

of said first cells to one of said foreign cells;

said handoff communication being in accordance with a data mechanism, said

data mechanism comprising a container structure comprising content expressed in the

foreign communications protocol so that the node structure can serve as a conduit for

the container and need not understand the content of the container structure; and A

radio access network as in claim 41,

wherein the container structure comprises a dedicated data mapped structure

generic to said radio access network and said foreign communication system such that

said generic data mapped structure transports both handover data content unique to

said first communication protocol and handover data content unique to said foreign

communication protocol.

49. (Currently amended) A radio access network as in claim [[41]] 48, wherein

the radio access network node fills the container structure to include broadcast system

information.

50. (Currently amended) A radio access network as in claim [[41]] 48, wherein

the multi-mode radio fills the container structure to include mobile radio capabilities

information.

51. (Currently amended) A radio access network as in claim [[41]] 48, wherein

the radio access network node fills the container structure to include neighboring cell

information.

52. (Currently amended) A radio access network as in claim [[41]] 48, wherein

the radio access network node fills the container structure to include neighboring cell

measurement instructions.

53. (Currently amended) A radio access network as in claim [[41]] 48, wherein

Page 4 of 13

the mobile radio fills the container structure to include neighboring cell measurement results.

54. (Currently amended) A radio access network as in claim [[41]] 48, wherein the radio access network node fills the container structure to include handoff command information.

55. (Currently amended) A radio access network as in claim [[41]] 48, wherein the second network is a core network.

56-62. (Cancelled)

63. (Currently amended) A method of operating a mobile radio network, the mobile radio network comprising:

a radio access network having a radio access network node structure for communicating using an associated first communication protocol with a multi-mode mobile radio in a first cell serviced by said radio access network; and

a second network having an associated foreign communication protocol for communicating to the multi-mode mobile radio in at least one foreign cell neighboring said first cell and serviced by said second network according to said foreign communication protocol, said radio network and said second network being in handoff communication with each other to handoff said mobile radio when said mobile radio commutes from the first cell to one of said foreign cells;

the method comprising:

providing a data mechanism for facilitating said handoff communication, said data mechanism comprising a container structure;

<u>including in the container structure content expressed in the foreign communications protocol;</u>

using the node structure as a conduit for communicating the contents of the container to the multi-mode mobile radio and wherein the node structure need not

understand the content of the container structure; A method as in claim 56, further comprising

providing the container structure with a dedicated data mapped structure generic to said radio access network and said foreign communication system such that said generic data mapped structure transports both handover data content unique to said first communication protocol and handover data content unique to said foreign communication protocol.

64. (Currently amended) A method as in claim [[56]] <u>63</u>, further comprising the radio access network node filling the container structure to include broadcast system information.

65. (Currently amended) A method as in claim [[56]] 63, further comprising the multi-mode radio filling the container structure to include mobile radio capabilities information.

66. (Currently amended) A method as in claim [[56]] 63, further comprising the radio access network node filling the container structure to include neighboring cell information.

67. (Currently amended) A method as in claim [[56]] <u>63</u>, further comprising the radio access network node filling the container structure to include neighboring cell measurement instructions.

68. (Currently amended) A method as in claim [[56]] 63, further comprising the mobile radio filling the container structure to include neighboring cell measurement results.

69. (Currently amended) A method as in claim [[56]] 63, further comprising the radio access network node filling the container structure to include handoff command

information.

- 70. (Currently amended) A method as in claim [[56]] 63, wherein the second network is a core network.
- 71. (Currently amended) A method of operating a mobile radio network, the mobile radio network comprising:
- a radio access network having a radio access network node structure for communicating using an associated first communication protocol with a multi-mode mobile radio in a first cell serviced by said radio access network; and
- a second network having an associated foreign communication protocol for communicating to the multi-mode mobile radio in at least one foreign cell neighboring said first cell and serviced by said second network according to said foreign communication protocol, said radio network and said second network being in handoff communication with each other to handoff said mobile radio when said mobile radio commutes from the first cell to one of said foreign cells;

the method comprising:

providing a data mechanism for facilitating said handoff communication, said data mechanism comprising a container structure;

<u>including in the container structure content expressed in the foreign</u> <u>communications protocol;</u>

using the node structure as a conduit for communicating the contents of the container to the multi-mode mobile radio and wherein the node structure need not understand the content of the container structure; A method as in claim 56, further comprising:

exchanging handoff-specific information between second network associated with, respectively, said first radio communication protocol and said foreign communication protocol, and

filling said handoff-specific information container between said second network with said handoff information in a form particular to said foreign radio communication

protocol type.

72-74. (Cancelled)

75. (New) A radio access network as in claim 34, wherein the content of the

container structure comprises communication parameters for the foreign communication

system.

76. (New) A radio access network as in claim 75, wherein the communication

parameters for the foreign communication system are written by the foreign

communication system.

77. (New) A radio access network as in claim 34, wherein the content of the

container structure includes a message or command dictated by the foreign

communications protocol.

78. (New) A radio access network as in claim 77, wherein the command is a

handover command.

79. (New) A radio access network as in claim 34, wherein the radio access

network is a Universal Mobile Telephone System (UMTS) radio access network and the

foreign communication system is one of a Group Special Mobile (GSM) or Personal

Digital Cellular (PDC) communication system.

80. (New) A radio access network as in claim 34, wherein the radio access

network is a third generation system and the foreign communication system is second

generation system.

81. (New) A radio access network as in claim 48, wherein the content of the

container structure comprises communication parameters for the foreign communication

Page 8 of 13

system.

82. (New) A radio access network as in claim 81, wherein the communication

parameters for the foreign communication system are written by the foreign

communication system.

83. (New) A radio access network as in claim 48, wherein the content of the

container structure includes a message or command dictated by the foreign

communications protocol.

84. (New) A radio access network as in claim 83, wherein the command is a

handover command.

85. (New) A radio access network as in claim 48, wherein the radio access

network is a Universal Mobile Telephone System (UMTS) radio access network and the

foreign communication system is one of a Group Special Mobile (GSM) or Personal

Digital Cellular (PDC) communication system.

86. (New) A radio access network as in claim 48, wherein the radio access

network is a third generation system and the foreign communication system is second

generation system.

87. (New) A method as in claim 63, further comprising including communication

parameters for the foreign communication system in the content of the container

structure.

88. (New) A method as in claim 87, further comprising the foreign

communication system writing the communication parameters for the foreign

communication system.

Page 9 of 13

EUS/GJ/P/10-7525

89. (New) A method as in claim 63, further comprising including a message or

command dictated by the foreign communications protocol in the content of the

container structure.

90. (New) A method as in claim 89, further comprising including a handover

command in the content of the container structure.

91. (New) A method as in claim 63, wherein the radio access network is a

Universal Mobile Telephone System (UMTS) radio access network and the foreign

communication system is one of a Group Special Mobile (GSM) or Personal Digital

Cellular (PDC) communication system.

92. (New) A method as in claim 63, wherein the radio access network is a third

generation system and the foreign communication system is second generation system.

\* \* \*